

Select *CoverWise™ Green Vinyl* for superior Environmental Performance with low emissions

CoverWise™ Green Vinyl

CoverWise™ Green Vinyl is formulated to meet stringent indoor air quality standards including:
 GreenGuard™¹
 USEPA, OSHA, State of Washington
 LEEDS

CoverWise™ Green Vinyl also will meet:
 All Type II wallcovering standards
 Class "A" flame rating – ASTM E-84 Test

Free of Toxic Heavy Metals

Obtain all the benefits of PVC while eliminating health and environmental concerns of heavy metals. Our film is formulated to contain no lead, chromium, nickel, mercury or cadmium.

Low VOC Emissions

CoverWise™ Green Vinyl has lower VOC emissions than traditional film, providing your customers improved air quality.

Lower Odor than standard vinyl

Improved Environmental Processing

Customize your product today!

Ask for any color, embossing, thickness or width!



CoverWise™ Films

Customized Solutions
 for Commercial Wallcovering

Use O'Sullivan Films *CoverWise™* Films for Interior Solutions including wallcoverings, flooring, window shades, decorative laminates, and specialty applications.

Property	Test Method	Standard	<i>Coverwise™</i> Green Results*
Elongation at Break	ASTM D882	250% min.	300%
Tensile at Break	ASTM D882	3000 lb/in ² min.	3500 lb/in ²
Tear Strength	ASTM D751	60 lb/in min.	70 lb/in
Cold Crack Resistance	Federal Spec. CCC-W-408D	No change at 20°F	Pass
Dimensional Stability	Federal Spec. CCC-W-408D	- 2% max.	- 2.0%
TVOC Air Emissions	AQS Testing	< 500 µg/m ³	350 µg/m ³
Aldehyde Air Emission	AQS Testing	< 0.05 ppm	Not Detected

* Typical test results for commercial wallcovering (0.008" Opaque Film). Values considered to be nominal and do not constitute a warranty, specification or fitness for particular purpose.

For More Information Contact:

O'Sullivan Films

Phone: 800-894-0426
 Fax: 540-722-2695
 joe.cipullo@osul.com
 www.osul.com

S230714

¹ GreenGuard™ is a certification mark of Air Quality Sciences, Inc.